

ATTACK Z 200/300 HP

Technical data

Parameter	Unit	Z 200 HP	Z 300 HP
Nominal capacity	l	200	300
Weight without water	kg	90	116
Nominal operating pressure	MPa	0.6	0.6
Maximum safety-valve opening pressure	MPa	0.7	0.7
Minimum required water pressure	MPa	0.01	0.01
Standby energy consumption at 65 °C	Wh/24 h	1900	2500
Heated volume of lower heat exchanger	l	200	300
Lower heat-exchanger area	m ²	1	1.5
Lower heat-exchanger volume	l	5.7	8.5
Operating pressure of lower heat exchanger	MPa	0.6	0.6
Heated volume of upper heat exchanger	l	90	130
Upper heat-exchanger area	m ²	0.8	1
Upper heat-exchanger volume	l	4.6	5.7
Operating pressure of upper heat exchanger	MPa	0.6	0.6
Tank material	—	Enamelled steel sheet	Enamelled steel sheet
Heat-exchanger material	—	Enamelled steel tube	Enamelled steel tube
Corrosion protection	—	Fired enamel + active anode	Fired enamel + active anode
Cold- and hot-water connection	—	G3/4	G3/4
Circulation connection	—	G3/4	G3/4

Parameter	Unit	Z 200 HP	Z 300 HP
Connection for electric element	—	Rp6/4	Rp6/4
Heat-exchanger connection	—	Rp3/4	Rp3/4
Thermometer and sensor connections	—	Rp1/2	Rp1/2